

Maintenance Guide for PVC Bathroom Cabinet

1. Daily Cleaning

- **Routine Cleaning:** Wipe with a soft cloth dipped in soapy water, mild detergent or warm water. Avoid wiping with a dry cloth to prevent surface scratches.

- **Stain Removal:**

- ◆ Oil stains: Wipe off with a soft cloth first, then clean with a neutral detergent or special cleaner.

- ◆ Acidic liquids: Rinse with water immediately, then soak in ammonium solution or neutral sodium carbonate solution, and finally wash with warm water.

- ◆ Rainbow marks: Clean with warm water and neutral detergent (caused by excessive use of cleaners or grease).

- ◆ Stubborn stains: Clean with 10% nitric acid solution or special abrasive detergent.

2. Prohibited Practices

- Do not use abrasive cleaners, hard cloths, steel wool or paper towels for wiping to avoid damaging the surface.

- Avoid direct sunlight to prevent fading and deformation of PVC materials.

- Avoid prolonged exposure to humid environments. Keep cabinet doors open for ventilation and drying after use.

- Do not place heavy items to prevent cabinet deformation.

3. Regular Maintenance

- Wipe the surface with a special care agent monthly to enhance stain resistance.

- Check hardware (such as hinges and slides). Tighten them promptly if loose, and replace them immediately if damaged.

- For minor scratches, use a professional repair pen or repair paste for repair. For severe damage, it is recommended to contact professional personnel for treatment.

Maintenance Guide for Resin Basin

1. Daily Cleaning

- **Routine Cleaning:** Wipe with a soft damp cloth dipped in neutral cleaners (such as hand soap, body wash). Avoid using cleaners containing alcohol, acetone, strong acids or alkalis.
- **Limescale Removal:** Spray with white vinegar or special limescale cleaner, let it sit for 5-10 minutes, then wipe with a soft cloth.
- **Stain Removal:**
 - ◆ Mild stains: Wipe with toothpaste or baking soda paste, then rinse with water.
 - ◆ Stubborn stains: Use a special resin cleaner, or gently sand with fine sandpaper (400 grit or above), then polish with polishing paste.

2. Prohibited Practices

- ◆ Avoid scratching the surface with sharp objects (such as razors, scissors).
- ◆ Avoid direct contact with high-temperature objects (such as kettles, hair dryers) to prevent deformation and yellowing of the countertop.
- ◆ Avoid prolonged contact with dark liquids (such as coffee, tea) to prevent staining.
- ◆ Do not wipe with steel wool or rough sponges to avoid scratches.

3.Regular Maintenance

- Apply a special resin care agent every quarter to form a protective film and enhance stain resistance.
- For deep scratches, sand with 800-grit sandpaper first, then polish with 1200-grit sandpaper, and finally apply the care agent.
- If the countertop turns yellow, soak it in a diluted bleach solution (1:10) for 10-15 minutes, then rinse with water.